NAVIGATION

MyGuide 3500 GO

Introduction

Wherever you go, do not leave without the Typhoon MyGuide 3500 GO. The Typhoon MyGuide 3500 GO is the ideal navigation system to accompany you when you drive or looking for a location.
Landscape display for natural view and buttons on the sides for easy access and operation. GPS antenna is flippable for operation and storage.

Features

- Intel® Xscale 300MHz processor
- 32MB Flash ROM, and 64MB SDRAM memory
- Windows® CE .net 4.2 operating system
- 3.5" Colour transflective LCD, LED backlight display
- 320 x 240, 65K colours, QVGA resolution
- Landscape format
- 18 x 18mm patch antenna
- Built-in GPS module, SiRFStarII chip with XTrack
- SD / MMC slot up to 1 GB capacity
- Rechargeable Lithium-ion battery

Specifications

- CPU: Intel PXA-255 300 MHz
- Video -
- Display: 3.5" Color Transflective LCD, LED Backlight with Antiglare
- Resolution: 320 ´ 240, 65K colors, QVGA resolution, Landscape
- Memory -
- ROM: 32MB Strata Flash ROM
- RAM: 64MB SDRAM
- Communication: SiRF GPS module built-in + Patch antenna
- Antenna -
- 25 x 25 mm Patch antenna with extended antenna jack
- Input / Output -
- Touch Panel: Resistive type Touch panel
- Input Method: Stylus pen / On-Screen Keyboard
- Speaker: Built-in loud speaker x 1
- Headphone: 3.5mm jack x 1
- Microphone: Built-in type microphone x 1 (Mono)
- TMC: Reserve function
- SD / MMC: For SD and compatible with MMC cards
- InfraRed: InfraRed for remote control
- USB: USB v1.1 (Client) for fast data transmission
- Buttons / Switch - Power On/Off, Volume Control Wheel (Jog-dial), Operating Button (Blue LED implanted), 4-way navigation Pad + Enter (Blue LED implanted), Mute button, Hardware Reset Switch, System Reset button
- Indicator: LED (Dual Color); Battery Charging - Amber (Static); Battery Full - Green (Static)
- Battery -
- Type: Un-swappable rechargeable Lithium battery cell, 1350 mAh
- Charging time: 3.5 ~ 4.0 hours (single battery pack)
- AC to DC Adapter: Input
- 100~240VAC, Output
  5VDC, 1A
- Car Charger: Input 10 ~ 30V, 1.3A Max, Output, 5V, 1A
- Certification & Regulation: FCC, CE, BSMI, VCCI, CCC, MIC, C-Tick
- Dimension: 137.8 mm (Length) x 71.98~78.18 mm (Width) x 25.7mm (Height)
- Weight:~ 200 g Operating temperature: 0~40°C
- Humidity: 0~90%, Non-Condense
- Operation System: Microsoft Windows® CE .Net 4.2 Core version

EAN Code:40 19337 97350 1

Art. no. 97350